

		WORKMASTER™ SERIES			
MODEL		25S	25	35	40
<b>Engine</b>					
Emissions level	hp (kW)	T4B Final	T4B Final	T4B Final	T4B Final
Gross horsepower	rpm	24.7 [18.4]	24.4 [18.2]	35 [26.1]	40 [29.2]
Rated speed		3000	2500	2600	2600
No. of cylinders		3	3	3	3
Aspiration	cu.in. (L)	Natural	Natural	Turbo	Turbo
Displacement		77.3 [1.26]	80.4 [1.3]	114.7 [1.9]	114.7 [1.9]
Alternator	amps	50	50	70	70
Fuel tank	gal. (L)	6.6 [25]	7.4 [28]	7.4 [28]	7.4 [28]
<b>PTO</b>					
PTO horsepower	hp (kW)	17.2 [12.8]	19.2 [14.3] Gear 17.1 [12.8] HST	29.7 [22.1] Gear / 28.0 [20.9] HST	34.0 [25.4] Gear / 32.0 [23.9] HST
PTO speed	rpm	540	540	540	540
PTO type		Independent Electro-Hydraulic Engagement			
Mid-PTO		●	Standard on HST / Optional on Gear		
Mid-PTO speed	rpm	2500	2000	2000	2000
<b>Transmission</b>					
Choice 1		2 Range Hydrostatic/Dual Pedal	12x12 Gear	12x12 Gear	12x12 Gear
Choice 2		—	3-Range Hydrostatic / Dual Pedal		
Maximum forward speed	mph (kph)	9.1 [14.7]	13.8 [22.2] Gear 15.3 [24.7] HST	14.2 [22.9] Gear / 14.8 [23.9] HST	
Cruise control		Standard HST	Standard HST	Standard HST	Standard HST
Gear/shuttle type		Synchro	Synchro	Synchro	Synchro
Rear diff-lock engagement		Mechanical	Mechanical	Mechanical	Mechanical
Brake type		Wet, Multi-Disc	Wet, Multi-Disc	Wet, Multi-Disc	Wet, Multi-Disc
<b>Hydraulics &amp; 3-point</b>					
Implement hydraulic flow	gpm (lpm)	4.6 [17.4]	7.9 [30]	8.2 [31]	8.2 [31]
Steering hydraulic flow	gpm (lpm)	2.1 [8]	4.6 [17.5] Gear 4.6 [17.5] HST	4.2 [15.9] Gear / 5.3 [19.9] HST	
Total Flow	gpm (lpm)	6.7 [25.4]	12.5 [47.5] Gear 12.5 [47.5] HST	12.4 [46.8] Gear / 13.5 [50.8] HST	
Remote Valves		1 Opt.	1 or 2 Opt.	1 or 2 Opt.	1 or 2 Opt.
3-Point hitch		Chain Type Stabilizers / Fixed Link Ends	Telescopic Stabilizer / Fixed Link Ends		
3-Point lift capacity @ ball ends	lbs. (kg)	992 (450)	1808 (820)	1808 (820)	1808 (820)
3-Point lift capacity @ 24 in. (610 mm) behind ball ends	lbs. (kg)	728 (330)	1433 (650)	1433 (650)	1433 (650)
3-Point linkage		Category I	Category I	Category I	Category I
<b>Front Axle Options</b>					
Four-Wheel Drive		●	●	●	●
<b>Dimensions &amp; Weight</b>					
Wheelbase	in. (mm)	56.1 [1425]	65.9 [1674]	67.5 [1715]	67.5 [1715]
Length	in. (mm)	97.4 [2473]	117.2 [2976]	121 [3074]	121 [3074]
Width	in. (mm)	46.7 [1187]	54.1 [1374]	66.5 [1689]	66.5 [1689]
Height (top of ROPS or Cab)	in. (mm)	87.4 [2220]	88.2 [2241]	87.7 [2227]	87.7 [2227]
Weight	lbs. (kg)	ROPS: 1444 [655] CAB: 1805 [819]	2469 [1120]	3067 [1391]	3067 [1391]

● Standard ○ Optional — Not available