

900 SERIES AIR- AND LIQUID-COOLED FRONTMOUNT™

The ultimate Contour-Cut FrontMount™ performer

QuikAjust Tilt™ levers with 9-in. adjustment range



LIMITED WARRANTY†
3 YEAR
 —UNLIMITED—
 COMMERCIAL
 LIMITED WARRANTY†
4 YEAR
 —800 HRS—
 RESIDENTIAL

Standard PowerFold® Electric Deck Lift. See Page 13 for more info.

900 D 1.3L

61 72

1.3L, 3-cylinder, liquid-cooled MaxTorque™ Clean Diesel horizontal crankshaft engine

932

61 72

962 cc, 3-cylinder, liquid-cooled MaxTorque™ horizontal crankshaft gasoline engine

940 EFI
ETC BIG BLOCK™

61 72

993 cc, air-cooled, V-Twin, Vanguard BIG BLOCK™ horizontal crankshaft gasoline engine

Mowing speeds up to 11 MPH and 7.20 acres/hr. based on 72" cutting width*
 For more details visit:
grasshoppermower.com/acres



■ DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated rear-discharge deck (Pg. 13)
- » Speed-Trimming™ heavy-duty roller (Pg. 8)
- » Taller steering levers
- » Full-flotation deck inserts (Pg. 13)
- » Foldable ROPS with seat belt
- » Turf tread tires
- » Multiple tail wheel options (Pg. 12)
- » Flat-proof 13 x 6.5-6 tail wheels (Pg. 38)
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Deck Tires (72" only) (Pg. 38)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Side discharge control kit (Pg. 8)
- » Air Dam kit – for dry, dusty conditions (Pg. 17)
- » Yellow beacon light (Pg. 21)
- » Filter Minder (940) (Pg. 38)
- » Armrest-mounted PowerFold® height adjustment switch
- » Radiator cleaning wand (900D and 932) (Pg. 7)
- » Engine block heater (900D and 932)
- » Footrest riser (Pg. 5)
- » Big Boy wide-seat conversion kit (900D and 932)

Perfect for fleet operations, these mowers combine True ZeroTurn™ maneuverability with a high-quality cut and versatile performance.

DURABILITY & LONGEVITY

The 900 Series mowers deliver more power, durability and maneuverability than any mower in its class. Choose from three high-power, high-efficiency engine options: 3-cylinder MaxTorque™ Clean Diesel; 3-cylinder MaxTorque™ gasoline or V-Twin gasoline engine featuring Electronic Fuel Injection (EFI) with Electronic Throttle Control (ETC). The horizontal crankshaft configuration with uniform cooling, airflow and internal lubrication adds performance life to the engine.

Robust 21cc pump-and-wheel motor systems are design-matched for Grasshopper mowers. They feature CoolFan™ cooling systems and 7-micron absolute filters. The pumps are driven by a single flat and serpentine, grooved belt. These features ensure smooth and responsive steering, less maintenance and 1,000-hour fluid change intervals.

MANICURED CUT

DuraMax® contour-cut decks are 5.5 inches deep and deliver a manicured cut and let you cover more ground in less time. The anvil-edged design offers exceptional durability. Decks easily convert from wide-pattern side discharge to optional mulching or vacuum collection systems. A dedicated rear-discharge deck is also available.

Excellent weight distribution, thanks to the low-center-of-gravity design, provides a smoother ride and lighter footprint for optimal traction and stability. The hydraulic deck lift raises the front of the deck or implement off the ground to clear curbs, trailer ramps and more.

COMFORT & ERGONOMICS

Change cutting height easily with the flip of the PowerFold® Electric Height Adjustment deck switch, standard on all 900 Series models. Use the same switch to fold up the deck for storage and easy maintenance.

The Cordura®-covered Premier Suspension Seat is standard on all 900 Series models and provides a custom fit for operators. The backrest tilts and includes adjustable lumbar support. Seat also adjusts to the operator's weight and slides fore and aft. Adjustable, foldable armrests are also standard. Adjustable cup holders let you tote along your favorite beverage. All models feature an electronic fuel gauge/hour meter on the console and two USB charging ports.

QuikAjust Tilt™ steering levers with “no tools” adjustment and provide a 9-inch range for maximum comfort and fit. Levers automatically return to neutral from forward or reverse when released.

Quickly attach a wide range of snow removal and turf renovation implements with the exclusive QuikConverter™ Implement System that saves time and labor on all your jobs and provides year-round productivity solutions. Power units include standard wiring harness for the addition of electric-powered implements.

900 SERIES AIR- AND LIQUID-COOLED FRONTMOUNT™ - SPECIFICATIONS

MODEL	Standard	Option	900D	932	940
ENGINE					
Type/Displacement/Cylinders					
Kubota MaxTorque™ diesel / 77.0 cu. in. (1.3L) / 3-cyl.	•				
Kubota MaxTorque™ gasoline / 58.7 cu. in. (962 cc) / 3-cyl.			•		
Vanguard BIG BLOCK™, closed-loop, Electronic Fuel Injection (EFI) with Electronic Throttle Control (ETC) / 60.6 cu. in. (993cc) / V-Twin					•
Crankshaft/Cooling System					
Horizontal with uniform cooling, airflow and internal lubrication / Liquid	•	•			
Horizontal with uniform cooling, airflow and internal lubrication / Air					•
Fuel/Capacity					
Diesel - No. 2 / 8.0 U.S. Gal. (30.3L)	•				
Gasoline - unleaded / 7.2 U.S. Gal. (27.3 l)			•		
Gasoline - unleaded / 14.4 U.S. Gal. (54.5 l) - twin 7.2-gal. (27.3 l) tanks with fuel selector					•
Air Cleaner					
Heavy-duty, remote mounted engine air cleaner with replaceable element.	•	•	•		
Filter Minder	•	•		•	
STARTER & ELECTRICAL SYSTEM					
Maintenance-Free Battery/Charging Capacity/Starter					
12 volt/40 amp/solenoid shift	•	•			
12 volt/20 amp/solenoid shift					•
Ignition					
Diesel quick heat glow plug	•				
Breakerless			•	•	
Interlock System					
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	•	•	•		
ULTIMATE OPERATOR STATION™					
Premier Suspension Seat					
Cordura® covered seat provides a custom fit for operators. The backrest tilts and includes adjustable lumbar support. Seat also adjusts to operator weight and slides fore and aft. Adjustable, foldable armrests are also standard.	•	•	•		
Suspension					
InFrame™ integrated multi-point suspension	•	•	•		
Console-Mounted Instruments					
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition, glow plug and push/pull PTO switches.	•				
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition and push/pull PTO switches. Choke integrated with throttle lever.				•	
Low engine oil pressure, engine code light and parking brake warning lights, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition and push/pull PTO switches.					•
Operator Protection					
ROPS with seat belt	•	•	•		
Operator Convenience					
Adjustable cup holder	•	•	•		
Work Lights					
LED	•	•	•		
TRANSMISSION & STEERING					
Type					
Rugged, design-matched G3 hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 21 cc piston-type pumps and Parker wheel motors. Single serpentine belt for more efficient power transfer.	•	•	•		
Transmission Fluid/Filtration					
Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals. / 7 micron absolute, spin-on filter.	•	•	•		
Speed					
0 - 11.0 mph (0 - 17.7 kph) forward	•	•	•		
0 - 6.0 mph (0 - 9.7 kph) reverse	•	•	•		
Turning Radius					
True zero degree, turns within own length with counter-rotating, independently powered drive wheels. Seat is pivot point.	•	•	•		
Steering					
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch adjustment range that automatically return to neutral from either forward or reverse position.	•	•	•		
Hydraulic Deck/Implement Lift switch integrated in right steering lever.	•	•	•		

MODEL	Standard	Option	900D	932	940
Brakes					
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	•	•	•		
Attachment Drive					
Telescoping, splined PTO shaft with two high-speed U-joints, Quik-D-Tatch® coupler and heavy-duty electric MagStop® blade clutch/brake.	•	•	•		
Temperature Sentry/high temperature clutch cut-out	•	•			
Wiring harness for electric-powered implements	•	•	•		
POWER UNIT TIRE SIZES					
Drive Wheels (4-ply rated): 24 x 12-12 bar tread, high flotation	•	•	•		
Drive Wheels (4-ply rated): 24 x 12-12, turf tread		•	•	•	
Tail Wheel: Wide-Stance, Single-Fork, 13 x 6.5-6 rib tread, pneumatic (2)	•	•	•		
POWER UNIT DIMENSIONS					
Width: 54.5 in. (138.4 cm)	•	•	•		
Length: 70.0 in. (177.8 cm)	•	•	•		
Height (ROPS): 69.5 in. (176.5 cm)	•	•	•		
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)	•	•			
Height (seat back/seat cushion): 49.0 in. (124.5 cm) / 32 in. (81.3 cm)	•	•			
Wheelbase: 54.5 in. (138.4 cm)	•	•	•		
WEIGHT					
Uncrated: 1150 lbs. (521.6 kg)	•				
Uncrated: 1100 lbs. (499.0 kg)			•		
Uncrated: 1140 lbs. (517.1 kg)				•	
DURAMAX® CONTOUR-CUT DECKS - Side Discharge or Dedicated Rear Discharge					
Model	Side Discharge/Rear Discharge	3661/3761R	3472/3572R		
Width of cut		61 in. (154.9 cm)	72 in. (182.9 cm)		
Width with deflector down		74.5 in. (189.2 cm)	85.5 in. (227.3 cm)		
Width with deflector raised		64.0 in. (162.6 cm)	75.0 in. (190.5 cm)		
Width - mulching or rear discharge		62.5 in. (158.8 cm)	73.5 in. (186.7 cm)		
Cutting Height*		1.25 to 5.0 in. (3.2 cm to 12.7 cm)			
PowerFold®		•	•		
Compatibility					
900D		•	•		
932		•	•		
940		•	•		
Construction (Robotic-welded steel)					
Tubular 2.25 in. x 4 in. boxed members with 0.25 in. gussets. Formed double thickness hardened steel (0.269 in. - 7.6% thicker than 0.25 in. (6.35 mm) truss spindle plane and (3) Sentry™ spindles and a triple-strength upper deck, over 1/2 in. thick in stress zones. Geometrically engineered design with 7 gauge skirts withstands the brunt of commercial mowing. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.					
Blades (MARBAIN®, 1/4-in. - High-lift blades standard)					
Tempered, alloy steel		(3) 21 in. (53.3 cm)	(3) 25 in. (63.5 cm)		
Spindle Assemblies					
2.5 cm (approx. 1 in.) O.D. shaft. Double bearings. Greasable from top of deck. Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion. Machined aluminum alloy housing.					
Spindle Housing - 8 in. (20.3 cm)-diameter with 6 bolt pattern					
Machined aluminum		•	•		
Blade Drive					
Maintenance-free gearbox with single Kevlar® V-belt and idler arm tensioning.					
Trimability					
(outside of tire to left trim side)		6.25 in. (15.9 cm)	12.25 in. (31.1 cm)		
Power Unit/Deck Length					
Deck (mowing position)		117.5 in. (298.5 cm)	120.5 in. (306.1 cm)		
Deck (folded up)		105.0 in. (266.7 cm)	107.0 in. (271.8 cm)		
Tire Size (4-ply rated): 11 x 4-5 (flat-proof)		•			
Tire Size (4-ply rated): 13 x 6.5-6 (rib tread, pneumatic)			•		
Weight Uncrated					
Side Discharge		445 lbs. (201.8 kg)	545 lbs. (247.2 kg)		
Mulching Package (Mulching package includes high-low mulching blades.)		36 lbs. (16.3 kg)	44 lbs. (20.0 kg)		

* 1.25" is reached with the combination of raising deck forks to top position AND moving tractor mowers lower by one set of holes. 5.0" height is reached using High Mow Kit #503289 for 61" deck, or #503287 for 72" deck.