

600 SERIES AIR-COOLED FRONTMOUNT™

Reliable economy to go the distance

LIMITED WARRANTY†
3 YEAR
 UNLIMITED
 COMMERCIAL
 LIMITED WARRANTY†
4 YEAR
 800 HRS
 RESIDENTIAL



Standard PowerFold® Electric Deck Lift.
See Page 13 for more info.

623T

48 52

694 cc, Kohler Command Pro V-Twin OHV horizontal crankshaft gasoline engine

A practical solution for your home or business, delivering the agile performance and quality cut only Grasshopper True ZeroTurn™ mowers can provide. Trim while you mow under shrubs and fences and enhance your precision cutting capabilities.

DURABILITY & LONGEVITY

The horizontal crankshaft configuration adds performance life to the engine.

Design-matched T-Drive™ hydrostatic drive systems, with AntiVibe Power Platform®, direct more power to the cutting deck and eliminate vibration. The CoolFan™ hydrostatic pump and filter cooling system partner with wheel motors for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

MANICURED CUT

5.5-inch deep 52-inch DuraMax® contour-cut decks, with anvil-edged design for exceptional durability, and the 4.5-inch deep 48-inch decks easily convert from wide-pattern side discharge to optional mulching or vacuum collection systems.

Change cutting height easily with the flip of the PowerFold® deck switch. Use the same switch to electrically fold up the deck for storage and easy maintenance.

COMFORT & ERGONOMICS

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar support and coil-spring suspension keeps the operator comfortably in control for all-day comfort.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit.

Quickly attach a wide range of seasonal implements with the exclusive QuikConverter™ Implement System to save time and labor on all your jobs.

Mowing speeds up to 8.5 MPH and 4.02 acres/hr. based on 52" cutting width*
 For more details visit:
grasshoppermower.com/acres



● 33 Series deck ▸ DuraMax® deck

OPTIONS

- Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- Down Discharge™ mulching packages
- Dedicated rear-discharge deck (52") (Pg. 13)
- Speed-Trimming™ heavy-duty roller (52") (Pg. 8)
- LED work lights (Pg. 38)
- Full-flotation deck inserts (Pg. 13)
- Taller steering levers
- QuikAdjust Tilt™ steering levers with "no tools" 9-in. comfort range (Pg. 5)
- Big Boy wide-seat conversion kit
- Premier suspension seat (Pg. 5)
- Adjustable cup holder
- Bar tread, low-pressure tires
- Michelin® X® Tweel® 22 x 11-12 Airless Turf Tires (Pg. 38)
- Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels (Pg. 38)
- QuikConverter™ implements (Pg. 18)
- Yellow beacon light (Pg. 21)
- Multiple tail wheel options (Pg. 12)
- Performance package including bar tread, low-pressure tires and wide-stance single-fork tail wheels
- QuikConverter™ implement capability with wiring harness (Pg. 18)
- PowerFold® height adjustment switch on armrest
- Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- Side discharge control kit (Pg. 8)
- Air Dam kit – for dry, dusty conditions (Pg. 17)

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements. Models may be shown with optional equipment. *Actual results may vary. †See warranty card for details.

AIR-COOLED 600 SERIES – SPECIFICATIONS

MODEL	● Standard ○ Option	623T
ENGINE		
Type/Displacement/Cylinders		●
Kohler Command Pro / 42.4 cu. in. (694cc) / V-Twin		
Crankshaft/Cooling System		
Horizontal / Air		●
Fuel/Capacity		
Gasoline - unleaded / 4.0 U.S. Gal. (15.1 l)		●
Air Cleaner		
Heavy-duty, remote-mounted engine air cleaner with replaceable element		●
STARTER & ELECTRICAL SYSTEM		
Maintenance-Free Battery/Charging Capacity/Starter		
12 volt/15 amp/solenoid shift		●
Ignition		
Breakerless		●
Interlock System		
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.		●
ULTIMATE OPERATOR STATION™		
Premium Comfort Seat		
Iso-mounted, high-back, multi-density, foam-padded Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.		●
Premier Suspension Seat		○
Suspension		
AntiVibe Power Platform® provides vibration-free experience.		●
Console-Mounted Instruments		
Low engine oil pressure and parking brake indicator lights, digital hour meter, ignition and push/pull PTO switches. Choke integrated with throttle lever.		●
Operator Protection		
Operator Protection Structure (OPS) with seat belt		●
Work Lights		
LED		○
TRANSMISSION & STEERING		
Type		
T-Drive™ hydrostatic transmission with tandem 12cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors. AntiVibe Power Platform® reduces vibration for the operator.		●
Transmission Fluid/Filtration		
Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals. / Integrated, replaceable, high-efficiency, fine-particle filter.		●
Speed		
0 - 8.5 mph (0 - 13.7 kph) forward		●
0 - 5.5 mph (0 - 8.9 kph) reverse		●
Turning Radius		
True zero degree, turns within own length with counter-rotating, independently powered drive wheels. Seat is pivot point.		●
Steering		
One- or two-handed operation with ComfortReach™ adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.		●
Brakes		
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.		●
Attachment Drive		
Telescoping PTO shaft with two high-speed U-joints, Quik-D-Tatch® coupler and heavy-duty electric MagStop blade clutch/brake.		●
POWER UNIT TIRE SIZES		
Drive Wheels: 20 x 10-8, turf tread		●
Drive Wheels: 22 x 11-10, turf tread		○
Drive Wheels (4-ply rated): 21 x 11-8 bar tread		○
Tail Wheel: Single-Fork, 13 x 6.5-6 rib tread, pneumatic		●
POWER UNIT DIMENSIONS		
Width: 47.0 in. (119.4 cm)**		●
**Add 1.0 in. (2.5 cm) for bar tread tires.		
Length: 61.0 in. (155.0 cm)		●
Height (Operator Protective Structure): 63.0 in. (160.0 cm)		●
Height (seat back): 43.5 in. (110.5 cm)		●
Height (seat cushion): 26.0 in. (66.0 cm)		●
Wheelbase: 46.0 in. (116.8 cm)		●

MODEL	● Standard ○ Option	623T
WEIGHT		
Uncrated: 750 lbs. (340.2 kg)		●
CONTOUR-CUT DECKS – Side Discharge or Dedicated Rear Discharge		
Model Side Discharge/Rear Discharge	3348	3452/3552R
Width of cut	48 in. (121.9 cm)	52 in. (132.1 cm)
Width with deflector down	61.5 in. (156.2 cm)	65.5 in. (166.5 cm)
Width with deflector folded up	51.0 in. (129.5 cm)	55.0 in. (139.7 cm)
Width - mulching or rear discharge	49.5 in. (125.7 cm)	53.5 in. (135.9 cm)
Cutting Height*	1.25 to 5.0 in. (3.2 cm to 12.7 cm)	
PowerFold®		●
Compatibility		
623T		●
Construction (Robotic-welded steel)		
Tubular 2.25-in. x 4-in. boxed members with 0.25-in. gussets. Geometrically engineered design with 7-gauge skirts withstands the brunt of commercial mowing. (3) Sentry™ spindles and a triple-strength upper deck, over 0.50-in. thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.		●
Formed double thickness hardened steel truss spindle plane is 0.2391-in. - equal to 3-gauge (6.07 mm)		●
Formed double thickness hardened steel truss spindle plane is 0.269-in. - 7.6% thicker than 0.25-in. (6.35 mm)		●
DuraMax® deck		●
Blades (MARBAIN®, 1/4-in. – High-lift blades standard)		
Tempered, alloy steel	(2) 18 in. (45.7 cm) (1) 15 in. (38.1 cm)	(3) 18 in. (45.7 cm)
Sentry™ Spindle Assemblies		
Spindle head designed to eliminate fiber wrap. Machined aluminum housing. 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings. Greasable from top of deck. (Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion - 52-in. deck only)		
Spindle Housing – 8-in. (20.3 cm)-diameter with 6-bolt pattern		
Machined aluminum		●
Blade Drive		
Maintenance-free gearbox with single Kevlar® V-belt and idler arm tensioning		
Trimability		
(Outside of tire to left trim side)	3.5 in. (8.9 cm)	2.5 in. (6.4 cm)
Power Unit/Deck Length		
Deck (mowing position)	100.0 in. (254.0 cm)	101.0 in. (256.5 cm)
Deck (folded up)	80.0 in. (203.2 cm)	85.5 in. (217.2 cm)
Tire Size (4-ply rated): 9 x 3.5-4 (flat-proof)		●
Weight Uncrated		
Side Discharge	290 lbs. (131.5 kg)	370 lbs. (167.8 kg)
Mulching Package (Mulching package includes high-low mulching blades.)	25 lbs. (11.3 kg)	29 lbs. (13.2 kg)

* 1.25" is reached with the combination of raising deck forks to top position AND moving tractor mounts lower by one set of holes. 5.0" height is reached using High Mow Kit #503289 for 52" deck.



Featured Model 623T with 52-inch DuraMax® deck

700 SERIES AIR-COOLED FRONTMOUNT™

Unexpected power when you need it most

QuikAdjust Tilt™ levers with 9-in. adjustment range

LIMITED WARRANTY†
3 YEAR
— UNLIMITED —
COMMERCIAL
LIMITED WARRANTY†
4 YEAR
— 800 HRS —
RESIDENTIAL



Standard PowerFold® Electric Deck Lift. See Page 13 for more info.

725KT

52 61

747 cc, Kohler Command Pro V-Twin OHV horizontal crankshaft gasoline engine

729BT

BIG BLOCK™

52 61 72

896 cc, V-Twin OHV Vanguard BIG BLOCK™ horizontal crankshaft gasoline engine

735BT

BIG BLOCK™

61 72

993 cc, V-Twin OHV Vanguard BIG BLOCK™ horizontal crankshaft gasoline engine

727T

EFI

52 61 72

747 cc, V-Twin Kohler Command Pro, Delphi®-based closed-loop, Electronic Fuel Injection horizontal crankshaft gasoline engine

Powerful and efficient with choices of Vanguard Big Block or Kohler EFI engines with horizontal crankshaft for longer performance life.

DURABILITY & LONGEVITY

For enhanced efficiency, consider the 727T EFI with closed-loop electronic fuel injection. A wide range of benefits include decreased fuel use, reliable hot and cold weather starts, reduced engine exhaust emissions and fewer fuel-related service issues.

Versatile and productive, with power to tackle tough jobs and plenty to spare thanks to the use of exclusive design-matched T-Drive™ and T6® hydrostatic drive systems. The tandem-pump drive train is direct-coupled to the engine to transmit more power to the cutting deck or implement. The innovative AntiVibe Power Platform® isolates the engine and drive system from the operator station providing an unprecedented, vibration-free environment eliminating fatigue for the operator.

The CoolFan™ hydrostatic pump and filter cooling system partner with wheel motors for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

MANICURED CUT

5.5-inch deep DuraMax® contour-cut decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection systems. A dedicated rear-discharge deck is also available.

Change cutting height easily with the flip of the PowerFold® deck switch. Use the same switch to electrically fold up the deck for storage and easy maintenance.

COMFORT & ERGONOMICS

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar support and coil-spring suspension keeps the operator comfortably in control for all-day comfort.

QuikAdjust Tilt™ steering levers with “no tools” adjustment provide a 9-inch range for maximum comfort and fit.

Quickly attach a wide range of seasonal implements with the exclusive QuikConverter™ Implement System to save time and labor on all your jobs. Power units include standard wiring harness for the addition of electric-powered implements.

Mowing speeds up to 10 MPH and 6.55 acres/hr. based on 72" cutting width*
For more details visit:
grasshoppermower.com/acres



► DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated rear-discharge deck (Pg. 13)
- » Speed-Trimming™ heavy-duty roller (Pg. 8)
- » Hydraulic deck lift (Pg. 13)
- » LED work lights (725KT) (Pg. 8)
- » Full-flotation deck inserts (Pg. 13)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Adjustable cup holder
- » Foldable ROPS with seat belt
- » Turf tires
- » Multiple tail wheel options (Pg. 12)
- » Flat-proof 13 x 6.5-6 tires (Pg. 38)
- » Michelin® X® Tweel® 22 x 11-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Deck Tires (72") (Pg. 38)
- » QuikConverter™ implements (Pg. 18)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Filter minder (729BT/735BT) (Pg. 38)
- » Air Dam kit – for dry, dusty conditions (Pg. 17)
- » QuikConverter™ implement capability with wiring harness (Pg. 18)
- » PowerFold® height adjustment switch on armrest
- » Side discharge control kit (Pg. 8)
- » Footrest riser (Pg. 5)

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements. Models may be shown with optional equipment. *Actual results may vary. †See warranty card for details

AIR-COOLED 700 SERIES-SPECIFICATIONS

MODEL	Standard	Option	725KT	727T	729BT	735BT
ENGINE						
Type/Displacement/Cylinders						
Kohler Command Pro / 45.6 cu. in. (747cc) / V-Twin	•					
Kohler Command Pro, Delphi®-based, closed-loop, Electronic Fuel Injection (EFI) / 45.6 cu. in. (747cc) / V-Twin		•				
B&S Vanguard Big Block / 54.7 cu. in. (896cc) / V-Twin				•		
B&S Vanguard Big Block / 60.6 cu. in. (993cc) / V-Twin					•	
Crankshaft/Cooling System						
Horizontal / Air	•	•	•	•	•	•
Fuel/Capacity						
Gasoline - unleaded / 7.2 U.S. Gal. (27.3 l)	•	•	•	•	•	•
Air Cleaner						
Heavy-duty, remote-mounted engine air cleaner with replaceable element	•	•	•	•	•	•
Heavy-duty cyclonic, remote-mounted engine dual air cleaner with replaceable element		•				
STARTER & ELECTRICAL SYSTEM						
Maintenance-Free Battery/Charging Capacity/Starter						
12 volt / 15 amp / solenoid shift	•					
12 volt / 20 amp / solenoid shift		•	•	•	•	•
Ignition						
Breakerless	•	•	•	•	•	•
Interlock System						
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	•	•	•	•	•	•
ULTIMATE OPERATOR STATION™						
Premium Comfort Seat						
Iso-mounted, high-back, multi-density, foam-padded Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	•	•	•	•	•	•
Premier Suspension Seat	○	○	○	○	○	○
Suspension						
AntiVibe Power Platform® provides vibration-free experience.	•	•	•	•	•	•
Console-Mounted Instruments						
Low engine oil pressure and parking brake warning lights, digital hour meter, work light, ignition and push/pull PTO switches. Choke integrated with throttle lever.	•		•	•	•	•
Low engine oil pressure, engine code light and parking brake warning lights, digital hour meter, ignition and push/pull PTO switches.		•				
Operator Protection/Convenience						
ROPS with seat belt	•	•	•	•	•	•
Adjustable cup holder	○	○	○	○	○	○
Work Lights						
LED	○	•	•	•	•	•
TRANSMISSION & STEERING						
Type						
T-Drive™ hydrostatic transmission with tandem 12cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors.	•					
T6® hydrostatic transmission with tandem 16cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors.		•	•	•	•	•
AntiVibe Power Platform® reduces vibration for the operator.	•	•	•	•	•	•
Transmission Fluid/Filtration						
Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals. / Integrated, replaceable, high-efficiency, fine-particle filter.	•	•	•	•	•	•
Speed						
0 - 9.0 mph (0 - 14.5 kph) forward	•					
0 - 10.0 mph (0 - 16.1 kph) forward		•	•	•	•	•
0 - 6.0 mph (0 - 9.7 kph) reverse	•	•	•	•	•	•
Turning Radius						
True zero degree, turns within own length with counter-rotating, independently powered drive wheels. Seat is pivot point.	•	•	•	•	•	•
Steering						
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch adjustment range that automatically return to neutral from either forward or reverse position.	•	•	•	•	•	•
Brakes						
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	•	•	•	•	•	•
Attachment Drive						
Telescoping PTO shaft with two high-speed U-joints, Quik-D-Tatch® coupler and heavy-duty electric MagStop blade clutch/brake.	•	•	•	•	•	•
Wiring harness for electric-powered implements	•	•	•	•	•	•

MODEL	Standard	Option	725KT	727T	729BT	735BT
POWER UNIT TIRE SIZES						
Drive Wheels (4-ply rated): 22 x 11-10 bar tread, high flotation	•	•	•	•	•	•
Drive Wheels (4-ply rated): 22 x 11-10, turf tread	○	○	○	○	○	○
Tail Wheel: Wide-Stance, Single-Fork, 13 x 6.5-6 rib tread, pneumatic (2)	•	•	•	•	•	•
Tail Wheel: Single-Fork, 13 x 6.5-6 rib tread, pneumatic	○	○	○	○	○	○
POWER UNIT DIMENSIONS						
Width: 50.0 in. (127.0 cm)	•	•	•	•	•	•
Length: 67.0 in. (170.2 cm)	•	•	•	•	•	•
Height (ROPS): 69.0 in. (175.3 cm)	•	•	•	•	•	•
Height (seat back/seat cushion): 46.0 in. (116.8 cm) / 30.5 in. (77.5 cm)		•				
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 30.5 in. (77.5 cm)	•	•	•	•	•	•
Wheelbase: 51.5 in. (130.8 cm)	•	•	•	•	•	•
WEIGHT						
Uncrated: 890 lbs. (403.7 kg)	•					
Uncrated: 915 lbs. (415 kg)		•				
Uncrated: 930 lbs. (421.8 kg)			•	•	•	•
DURAMAX® CONTOUR-CUT DECKS – Side Discharge or Dedicated Rear Discharge						
Model	Side Discharge/Rear Discharge	3452/3552R	3661/3761R	3472/3572R		
Width of cut	52 in. (132.1 cm)	61 in. (154.9 cm)	72 in. (182.9 cm)			
Width with deflector down	65.5 in. (166.5 cm)	74.5 in. (189.2 cm)	85.5 in. (227.3 cm)			
Width with deflector folded up	55.0 in. (139.7 cm)	64.0 in. (162.6 cm)	75.0 in. (190.5 cm)			
Width - mulching or rear discharge	53.5 in. (135.9 cm)	62.5 in. (158.8 cm)	73.5 in. (186.7 cm)			
Cutting Height*	1.25 to 5.0 in. (3.2 cm to 12.7 cm)					
PowerFold®	•	•	•	•	•	•
Compatibility						
725KT	•	•	•	•	•	•
727T	•	•	•	•	•	•
729BT	•	•	•	•	•	•
735BT	•	•	•	•	•	•
Construction (Robotic-welded steel) – Side discharge or optional Dedicated Rear Discharge						
Tubular 2.25 in. x 4 in. boxed members with 0.25 in. gussets. Formed double thickness hardened steel (0.269 in. - 7.6% thicker than 0.25 in. (6.35 mm) truss spindle plane and (3) Sentry™ spindles and a triple-strength upper deck, over 1/2 in. thick in stress zones. Geometrically engineered design with 7 gauge skirts withstands the brunt of commercial mowing. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.						
Blades (MARBAIN®, 1/4-in. – High-lift blades standard)						
Tempered, alloy steel	(3) 18 in. (45.7 cm)	(3) 21 in. (53.3 cm)	(3) 25 in. (63.5 cm)			
Spindle Assemblies						
2.5 cm (approx. 1 in.) O.D. shaft. Double bearings. Greasable from top of deck. Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.						
Spindle Housing – 8 in. (20.3 cm)-diameter with 6 bolt pattern						
Machined aluminum	•	•	•	•	•	•
Blade Drive						
Maintenance-free gearbox with single Kevlar® V-belt and idler arm tensioning.						
Trimability						
(outside of tire to left trim side)	1.0 in. (2.5 cm)	8.5 in. (21.6 cm)	13.75 in. (34.9 cm)			
Power Unit/Deck Length						
Deck (mowing position)	105.5 in. (268.0 cm)	109.5 in. (278.1 cm)	117.5 in. (298.5 cm)			
Deck (folded up)	88.5 in. (224.8 cm)	91.0 in. (231.1 cm)	104.0 in. (264.2 cm)			
Tire Size (4-ply rated): 9 x 3.5-4 (flat-proof)	•					
Tire Size (4-ply rated): 11 x 4-5 (flat-proof)		•				
Tire Size (4-ply rated): 13 x 6.5-6 (rib tread pneumatic)				•		
Weight Uncrated						
Side Discharge:	370 lbs. (167.8 kg)	420 lbs. (190.5 kg)	545 lbs. (247.2 kg)			
Mulching Package (Mulching package includes high-low mulching blades.)	29 lbs. (13.2 kg)	36 lbs. (16.3 kg)	44 lbs. (20.0 kg)			

* 1.25" is reached with the combination of raising deck forks to top position AND moving tractor mounts lower by one set of holes. 5.0" height is reached using High Mow Kit #503289 for 52" & 61" decks, or #503287 for 72" deck.

700 SERIES LIQUID-COOLED FRONTMOUNT™

Power and versatility that expand your capabilities

LIMITED WARRANTY†
3 YEAR
UNLIMITED
COMMERCIAL
LIMITED WARRANTY†
4 YEAR
800 HRS
RESIDENTIAL



QuikAdjust Tilt™ levers with 9-in. adjustment range

Standard PowerFold® Electric Deck Lift. See Page 13 for more info.

729T

52 61 72

962 cc, 3-cylinder MaxTorque™ horizontal crankshaft gasoline engine; T⁶ hydrostatic transmission

725DT

52 61 72

898 cc, 3-cylinder MaxTorque™ Clean Diesel horizontal crankshaft engine; T⁶ hydrostatic transmission

Perfect for fleet operations, these mowers combine True ZeroTurn™ maneuverability with a high-quality cut and versatile performance

DURABILITY & LONGEVITY

Designed for speed and durability, offering the powerful performance of a 3-cylinder Kubota gasoline or EPA Tier 4 Final-compliant diesel engine to master a wide range of grounds maintenance jobs and give you more savings opportunities. DuraMax® decks up to 72 inches deliver a manicured cut and let you cover more ground in less time, while a complete line of efficient snow removal and turf renovation implements work year-round.

The horizontal crankshaft configuration adds performance life to the engine.

Design-matched T⁶ hydrostatic drive systems with AntiVibe Power Platform®, direct more power to the cutting deck and eliminate vibration. The CoolFan™ hydrostatic pump and filter cooling system partner with wheel motors for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

MANICURED CUT

5.5-inch deep DuraMax® contour-cut decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection systems. A dedicated rear-discharge deck is also available.

Change cutting height easily with the flip of the PowerFold® deck switch. Use the same switch to electrically fold up the deck for storage and easy maintenance.

COMFORT & ERGONOMICS

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar support and coil-spring suspension keeps the operator comfortably in control for all-day comfort. An electronic fuel gauge/hour meter and two USB charging ports on the console, and an adjustable cup holder to make it convenient to tote along your favorite beverage.

QuikAdjust Tilt™ steering levers with “no-tools” adjustment provide a 9-inch range for maximum comfort and fit.

Quickly attach a wide range of seasonal implements with the exclusive QuikConverter™ Implement System to save time and labor on all your jobs. Power units include standard wiring harness for the addition of electric-powered implements.

Mowing speeds up to 10 MPH and 6.55 acres/hr. based on 72" cutting width*

For more details visit: grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated rear-discharge deck (Pg. 13)
- » Speed-Trimming™ heavy-duty roller (Pg. 8)
- » Hydraulic deck lift (Pg. 13)
- » Full-flotation deck inserts (Pg. 13)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Foldable ROPS with seat belt
- » Multiple tail wheel options (Pg. 12)
- » Turf tires
- » Michelin® X² Tweel® 22 x 11-12 Airless Turf Tires (Pg. 38)
- » Michelin® X² Tweel® 13 x 6.5-6 Airless Tail Wheels (Pg. 38)
- » Michelin® X² Tweel® 13 x 6.5-6 Airless Deck Tires (72") (Pg. 38)
- » Flat-proof 13 x 6.5-6 tires (Pg. 38)
- » QuikConverter™ implements (Pg. 18)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Filter minder (Pg. 38)
- » QuikConverter™ implement capability with wiring harness (Pg. 18)
- » Tine-Rake Dethatcher
- » PowerFold® height adjustment switch on armrest
- » Radiator cleaning wand (Pg. 7)
- » Block heater
- » Side discharge control kit (Pg. 8)
- » Air Dam kit - for dry, dusty conditions (Pg. 17)
- » Footrest riser (Pg. 5)

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements. Models may be shown with optional equipment. *Actual results may vary. †See warranty card for details

LIQUID-COOLED 700 SERIES - SPECIFICATIONS

MODEL	● Standard ○ Option	725DT	729T
ENGINE			
Type/Displacement/Cylinders			
Kubota MaxTorque™ / 54.8 cu. in. (898cc) / 3-cyl.	●		
Kubota MaxTorque™ / 58.7 cu. in. (962cc) / 3-cyl.			●
Crankshaft/Cooling System			
Horizontal / Liquid	●	●	
Fuel/Capacity			
Diesel - No. 2 / 8.0 U.S. Gal. (30.3 l)	●		
Gasoline - unleaded / 7.2 U.S. Gal. (27.3 l)		●	
Air Cleaner			
Heavy-duty, remote-mounted engine air cleaner with replacement element	●	●	
STARTER & ELECTRICAL SYSTEM			
Maintenance-Free Battery/Charging Capacity/Starter			
12 volt/40 amp/solenoid shift	●	●	
Ignition			
Breakerless			●
Diesel quick heat glow plug	●		
Interlock System			
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	●	●	
ULTIMATE OPERATOR STATION™			
Premium Comfort Seat			
Iso-mounted, high-back, multi-density, foam-padded Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	●	●	
Premier Suspension Seat	○	○	
Foldable armrests	●	●	
Suspension			
AntiVibe Power Platform® provides vibration-free experience.	●	●	
Console-Mounted Instruments			
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition, glow plug and push/pull PTO switches.	●		
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition and push/pull PTO switches. Choke integrated with throttle lever.			●
Operator Protection			
ROPS with seat belt	●	●	
Operator Convenience			
Adjustable cup holder	●	●	
Work Lights			
LED	●	●	
TRANSMISSION & STEERING			
Type			
T ⁶ hydrostatic transmission with tandem 16 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors.	●	●	
AntiVibe Power Platform® reduces vibration for the operator.	●	●	
Transmission Fluid/Filtration			
Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals. / Integrated, replaceable, high-efficiency, fine-particle filter.	●	●	
Speed			
0 - 10.0 mph (0 - 16.1 kph) forward	●	●	
0 - 6.0 mph (0 - 9.7 kph) reverse	●	●	
Turning Radius			
True zero degree, turns within own length with counter-rotating, independently powered drive wheels. Seat is pivot point.	●	●	
Steering			
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch adjustment range that automatically return to neutral from either forward or reverse position.	●	●	
Brakes			
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	●	●	
Attachment Drive			
Telescoping PTO shaft with two high-speed U-joints, Quik-D-Tatch® coupler and heavy-duty electric MagStop blade clutch/brake.	●	●	
Temperature Sentry/high temperature clutch cut-out	●	●	
Wiring harness for electric-powered implements	●	●	

MODEL	● Standard ○ Option	725DT	729T	
POWER UNIT TIRE SIZES				
Drive Wheels (4-ply rated): 22 x 11-10 bar tread, high flotation	●	●		
Drive Wheels (4-ply rated): 22 x 11-10, turf tread	○	○		
Tail Wheel: Wide-Stance, Single-Fork, 13 x 6.5-6 rib tread, pneumatic (2)	●	●		
POWER UNIT DIMENSIONS				
Width: 50.0 in. (127.0 cm)	●	●		
Length: 67.0 in. (170.2 cm)	●	●		
Height (ROPS): 69.0 in. (175.3 cm)	●	●		
Height (seat back/seat cushion): 46.0 in. (116.8 cm) / 30.5 in. (77.5 cm)	●	●		
Wheelbase: 51.5 in. (130.8 cm)	●	●		
WEIGHT				
Uncrated: 1000 lbs. (453.6 kg)	●	●		
DURAMAX® CONTOUR-CUT DECKS - Side Discharge or Dedicated Rear Discharge				
Model	Side Discharge/Rear Discharge	3452/3552R	3661/3761R	3472/3572R
Width of cut	52 in. (132.1 cm)	61 in. (154.9 cm)	72 in. (182.9 cm)	
Width with deflector down	65.5 in. (166.5 cm)	74.5 in. (189.2 cm)	85.5 in. (217.3 cm)	
Width with deflector raised	55.0 in. (139.7 cm)	64.0 in. (162.6 cm)	75.0 in. (190.5 cm)	
Width - mulching or rear discharge	53.5 in. (135.9 cm)	62.5 in. (158.8 cm)	73.5 in. (186.7 cm)	
Cutting Height*	1.25 to 5.0 in. (3.2 cm to 12.7 cm)			
PowerFold®	●	●	●	
Compatibility				
725DT	●	●	●	
729T	●	●	●	
Construction (Robotic-welded steel)				
Tubular 2.25 in. x 4 in. boxed members with 0.25 in. gussets. Formed double thickness hardened steel (0.269 in. - 7.6% thicker than 0.25 in. (6.35 mm) truss spindle plane and (3) Sentry™ spindles and a triple-strength upper deck, over 1/2 in. thick in stress zones. Geometrically engineered design with 7 gauge skirts withstands the brunt of commercial mowing. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.				
Blades (MARBAIN®, 1/4-in. - High-lift blades standard)				
Tempered, alloy steel	(3) 18 in. (45.7 cm)	(3) 21 in. (53.3 cm)	(3) 25 in. (63.5 cm)	
Spindle Assemblies				
2.5 cm (approx. 1 in.) O.D. shaft. Double bearings. Greasable from top of deck. Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.				
Spindle Housing - 8 in. (20.3 cm)-diameter with 6 bolt pattern				
Machined aluminum	●	●	●	
Blade Drive				
Maintenance-free gearbox with single Kevlar V-belt and idler arm tensioning.				
Trimability				
(outside of tire to left trim side)	1.0 in. (2.5 cm)	8.5 in. (21.6 cm)	13.75 in. (34.9 cm)	
Power Unit/Deck Length				
Deck (mowing position)	105.5 in. (268.0 cm)	109.5 in. (278.1 cm)	117.5 in. (298.5 cm)	
Deck (folded up)	88.5 in. (224.8 cm)	91.0 in. (231.1 cm)	104.0 in. (264.2 cm)	
Tire Size (4-ply rated): 9 x 3.5-4 (flat-proof)	●			
Tire Size (4-ply rated): 11 x 4-5 (flat-proof)		●		
Tire Size (4-ply rated): 13 x 6.5-6 (rib tread, pneumatic)			●	
Weight Uncrated				
Side Discharge:	370 lbs. (167.8 kg)	420 lbs. (190.5 kg)	545 lbs. (247.2 kg)	
Mulching Package (Mulching package includes high-low mulching blades.)	29 lbs. (13.2 kg)	36 lbs. (16.3 kg)	44 lbs. (20.0 kg)	

* 1.25" is reached with the combination of raising deck forks to top position AND moving tractor mounts lower by one set of holes. 5.0" height is reached using High Mow Kit #503289 for 52" & 61" decks, or #503287 for 72" deck.



Featured Model 729T with 61-inch DuraMax® deck

900 SERIES AIR- AND LIQUID-COOLED FRONTMOUNT™

The ultimate Contour-Cut FrontMount™ performer

QuikAdjust Tilt™ levers with 9-in. adjustment range



LIMITED WARRANTY†
3 YEAR
UNLIMITED
COMMERCIAL
LIMITED WARRANTY†
4 YEAR
800 HRS
RESIDENTIAL

Standard PowerFold® Electric Deck Lift. See Page 13 for more info.

900 D 1.3L
61 72
1.3L, 3-cylinder, liquid-cooled MaxTorque™ Clean Diesel horizontal crankshaft engine

932
61 72
962 cc, 3-cylinder, liquid-cooled MaxTorque™ horizontal crankshaft gasoline engine

940 EFI ETC BIG BLOCK™
61 72
993 cc, air-cooled, V-Twin, Vanguard BIG BLOCK™ horizontal crankshaft gasoline engine

Mowing speeds up to 11 MPH and 7.20 acres/hr. based on 72" cutting width*
For more details visit: grasshoppermower.com/acres



■ DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated rear-discharge deck (Pg. 13)
- » Speed-Trimming™ heavy-duty roller (Pg. 8)
- » Taller steering levers
- » Full-flotation deck inserts (Pg. 13)
- » Foldable ROPS with seat belt
- » Turf tread tires
- » Multiple tail wheel options (Pg. 12)
- » Flat-proof 13 x 6.5-6 tail wheels (Pg. 38)
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Deck Tires (72" only) (Pg. 38)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Side discharge control kit (Pg. 8)
- » Air Dam kit – for dry, dusty conditions (Pg. 17)
- » Yellow beacon light (Pg. 21)
- » Filter Minder (940) (Pg. 38)
- » Armrest-mounted PowerFold® height adjustment switch
- » Radiator cleaning wand (900D and 932) (Pg. 7)
- » Engine block heater (900D and 932)
- » Footrest riser (Pg. 5)
- » Big Boy wide-seat conversion kit (900D and 932)

Perfect for fleet operations, these mowers combine True ZeroTurn™ maneuverability with a high-quality cut and versatile performance.

DURABILITY & LONGEVITY

The 900 Series mowers deliver more power, durability and maneuverability than any mower in its class. Choose from three high-power, high-efficiency engine options: 3-cylinder MaxTorque™ Clean Diesel; 3-cylinder MaxTorque™ gasoline or V-Twin gasoline engine featuring Electronic Fuel Injection (EFI) with Electronic Throttle Control (ETC). The horizontal crankshaft configuration with uniform cooling, airflow and internal lubrication adds performance life to the engine.

Robust 21cc pump-and-wheel motor systems are design-matched for Grasshopper mowers. They feature CoolFan™ cooling systems and 7-micron absolute filters. The pumps are driven by a single flat and serpentine, grooved belt. These features ensure smooth and responsive steering, less maintenance and 1,000-hour fluid change intervals.

MANICURED CUT

DuraMax® contour-cut decks are 5.5 inches deep and deliver a manicured cut and let you cover more ground in less time. The anvil-edged design offers exceptional durability. Decks easily convert from wide-pattern side discharge to optional mulching or vacuum collection systems. A dedicated rear-discharge deck is also available.

Excellent weight distribution, thanks to the low-center-of-gravity design, provides a smoother ride and lighter footprint for optimal traction and stability. The hydraulic deck lift raises the front of the deck or implement off the ground to clear curbs, trailer ramps and more.

COMFORT & ERGONOMICS

Change cutting height easily with the flip of the PowerFold® Electric Height Adjustment deck switch, standard on all 900 Series models. Use the same switch to fold up the deck for storage and easy maintenance.

The Cordura®-covered Premier Suspension Seat is standard on all 900 Series models and provides a custom fit for operators. The backrest tilts and includes adjustable lumbar support. Seat also adjusts to the operator's weight and slides fore and aft. Adjustable, foldable armrests are also standard. Adjustable cup holders let you tote along your favorite beverage. All models feature an electronic fuel gauge/hour meter on the console and two USB charging ports.

QuikAdjust Tilt™ steering levers with "no tools" adjustment and provide a 9-inch range for maximum comfort and fit. Levers automatically return to neutral from forward or reverse when released.

Quickly attach a wide range of snow removal and turf renovation implements with the exclusive QuikConverter™ Implement System that saves time and labor on all your jobs and provides year-round productivity solutions. Power units include standard wiring harness for the addition of electric-powered implements.

900 SERIES AIR- AND LIQUID-COOLED FRONTMOUNT™ - SPECIFICATIONS

MODEL	Standard	Option	900D	932	940
ENGINE					
Type/Displacement/Cylinders					
Kubota MaxTorque™ diesel / 77.0 cu. in. (1.3L) / 3-cyl.	•				
Kubota MaxTorque™ gasoline / 58.7 cu. in. (962 cc) / 3-cyl.		•			
Vanguard BIG BLOCK™, closed-loop, Electronic Fuel Injection (EFI) with Electronic Throttle Control (ETC) / 60.6 cu. in. (993cc) / V-Twin				•	
Crankshaft/Cooling System					
Horizontal with uniform cooling, airflow and internal lubrication / Liquid	•	•			
Horizontal with uniform cooling, airflow and internal lubrication / Air				•	
Fuel/Capacity					
Diesel - No. 2 / 8.0 U.S. Gal. (30.3L)	•				
Gasoline - unleaded / 7.2 U.S. Gal. (27.3 l)		•			
Gasoline - unleaded / 14.4 U.S. Gal. (54.5 l) - twin 7.2-gal. (27.3 l) tanks with fuel selector			•		
Air Cleaner					
Heavy-duty, remote mounted engine air cleaner with replaceable element.	•	•	•		
Filter Minder	•	•	•	•	•
STARTER & ELECTRICAL SYSTEM					
Maintenance-Free Battery/Charging Capacity/Starter					
12 volt/40 amp/solenoid shift	•	•			
12 volt/20 amp/solenoid shift				•	
Ignition					
Diesel quick heat glow plug	•				
Breakerless		•	•		
Interlock System					
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	•	•	•		
ULTIMATE OPERATOR STATION™					
Premier Suspension Seat					
Cordura®-covered seat provides a custom fit for operators. The backrest tilts and includes adjustable lumbar support. Seat also adjusts to operator weight and slides fore and aft. Adjustable, foldable armrests are also standard.	•	•	•		
Suspension					
InFrame™ integrated multi-point suspension	•	•	•		
Console-Mounted Instruments					
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition, glow plug and push/pull PTO switches.	•				
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition and push/pull PTO switches. Choke integrated with throttle lever.		•			
Low engine oil pressure, engine code light and parking brake warning lights, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition and push/pull PTO switches.				•	
Operator Protection					
ROPS with seat belt	•	•	•		
Operator Convenience					
Adjustable cup holder	•	•	•		
Work Lights					
LED	•	•	•		
TRANSMISSION & STEERING					
Type					
Rugged, design-matched G3 hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 21cc piston-type pumps and Parker wheel motors. Single serpentine belt for more efficient power transfer.	•	•	•		
Transmission Fluid/Filtration					
Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals. / 7 micron absolute, spin-on filter.	•	•	•		
Speed					
0 - 11.0 mph (0 - 17.7 kph) forward	•	•	•		
0 - 6.0 mph (0 - 9.7 kph) reverse	•	•	•		
Turning Radius					
True zero degree, turns within own length with counter-rotating, independently powered drive wheels. Seat is pivot point.	•	•	•		
Steering					
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch adjustment range that automatically return to neutral from either forward or reverse position.	•	•	•		
Hydraulic Deck/Implement Lift switch integrated in right steering lever.	•	•	•		

MODEL	Standard	Option	900D	932	940
Brakes					
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	•	•	•		
Attachment Drive					
Telescoping, splined PTO shaft with two high-speed U-joints, Quik-D-Tatch® coupler and heavy-duty electric MagStop® blade clutch/brake.	•	•	•		
Temperature Sentry/high temperature clutch cut-out		•	•		
Wiring harness for electric-powered implements	•	•	•		
POWER UNIT TIRE SIZES					
Drive Wheels (4-ply rated): 24 x 12-12 bar tread, high flotation	•	•	•		
Drive Wheels (4-ply rated): 24 x 12-12, turf tread		•	•	•	
Tail Wheel: Wide-Stance, Single-Fork, 13 x 6.5-6 rib tread, pneumatic (2)	•	•	•		
POWER UNIT DIMENSIONS					
Width: 54.5 in. (138.4 cm)	•	•	•		
Length: 70.0 in. (177.8 cm)	•	•	•		
Height (ROPS): 69.5 in. (176.5 cm)	•	•	•		
Height (seat back/seat cushion): 47.0 in. (119.4 cm)/ 31.5 in. (80.0 cm)	•	•	•		
Height (seat back/seat cushion): 49.0 in. (124.5 cm)/ 32 in. (81.3 cm)		•	•	•	
Wheelbase: 54.5 in. (138.4 cm)	•	•	•		
WEIGHT					
Uncrated: 1150 lbs. (521.6 kg)		•			
Uncrated: 1100 lbs. (499.0 kg)			•		
Uncrated: 1140 lbs. (517.1 kg)				•	
DURAMAX® CONTOUR-CUT DECKS – Side Discharge or Dedicated Rear Discharge					
Model	Side Discharge/Rear Discharge	3661/3761R	3472/3572R		
Width of cut		61 in. (154.9 cm)	72 in. (182.9 cm)		
Width with deflector down		74.5 in. (189.2 cm)	85.5 in. (217.3 cm)		
Width with deflector raised		64.0 in. (162.6 cm)	75.0 in. (190.5 cm)		
Width - mulching or rear discharge		62.5 in. (158.8 cm)	73.5 in. (186.7 cm)		
Cutting Height*		1.25 to 5.0 in. (3.2 cm to 12.7 cm)			
PowerFold®		•	•		
Compatibility					
900D		•	•		
932		•	•		
940		•	•		
Construction (Robotic-welded steel)					
Tubular 2.25 in. x 4 in. boxed members with 0.25 in. gussets. Formed double thickness hardened steel (0.269 in. - 7.6% thicker than 0.25 in. (6.35 mm) truss spindle plane and (3) Sentry™ spindles and a triple-strength upper deck, over 1/2 in. thick in stress zones. Geometrically engineered design with 7 gauge skirts withstands the brunt of commercial mowing. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.					
Blades (MARBAIN®, 1/4-in. — High-lift blades standard)					
Tempered, alloy steel		(3) 21 in. (53.3 cm)	(3) 25 in. (63.5 cm)		
Spindle Assemblies					
2.5 cm (approx. 1 in.) O.D. shaft. Double bearings. Greasable from top of deck. Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion. Machined aluminum alloy housing.					
Spindle Housing – 8 in. (20.3 cm)-diameter with 6 bolt pattern					
Machined aluminum		•	•		
Blade Drive					
Maintenance-free gearbox with single Kevlar® V-belt and idler arm tensioning.					
Trimability					
(outside of tire to left trim side)		6.25 in. (15.9 cm)	12.25 in. (31.1 cm)		
Power Unit/Deck Length					
Deck (mowing position)		117.5 in. (298.5 cm)	120.5 in. (306.1 cm)		
Deck (folded up)		105.0 in. (266.7 cm)	107.0 in. (271.8 cm)		
Tire Size (4-ply rated): 11 x 4-5 (flat-proof)		•			
Tire Size (4-ply rated): 13 x 6.5-6 (rib tread, pneumatic)			•		
Weight Uncrated					
Side Discharge		445 lbs. (201.8 kg)	545 lbs. (247.2 kg)		
Mulching Package (Mulching package includes high-low mulching blades.)		36 lbs. (16.3 kg)	44 lbs. (20.0 kg)		

* 1.25" is reached with the combination of raising deck forks to top position AND moving tractor mounts lower by one set of holes. 5.0" height is reached using High Mow Kit #503289 for 61" deck, or #503287 for 72" deck.